



Adjoint Optimisation of Multi-Angle Achromatic Metalenses

Ma Weiyi, Onn Qi Huan

Introduction



Metalenses have **vast applications** (e.g. biomedical imaging, virtual reality)...^[1]



...but main issue arises in design: high degrees of freedom **complicates traditional optimisation**.

Low cost-effectiveness, as days needed to generate potentially sub-optimal designs.^[2]



Aims

Rapid developments into inverse design has advanced state-of-the-art in flat optics.

- a. Develop valid & inexpensive optimisation process** for efficient achromatic metalens design.
- b. Obtain optimised & fabricable designs** that maintain wide-spectrum **high-quality focusing**.

Methodology

Inverse Design


Given a desired response, what is the optimal structure?

- Maximise $f = |E_z(\mathbf{r}_0)|^2$ subject to Maxwell's equations

$$\nabla \cdot \epsilon \mathbf{E} = \rho, \nabla \cdot \mu \mathbf{H} = 0,$$

$$\nabla \times \mathbf{E} = -j\omega\mu\mathbf{H}, \nabla \times \mathbf{H} = \mathbf{J}_f + j\omega\epsilon\mathbf{E}$$


- Computational speedup **via Lorentz's reciprocity**; use adjoint electromagnetic field auxiliary to the direct field; backpropagate the intended field response to obtain structural updates



Optimisation Process

Setting up Electromagnetic Simulation

using open-source Python library MEEP w/ adjoint solver.^[3]



Gradient Calculations

with forward runs to evaluate f , then adjoint runs from focal point.

- Forward**: electromagnetic FDTD method using Yee lattice discretization
- Adjoint**: backpropagation of desired response through the metastructure

Optimisation algorithm: the **method of moving asymptotes**.^[4]

- Recast in epigraph form to ensure differentiability in maximin problem


$$\max f(x) = \max \min \{f_1(\mathbf{E}), f_2(\mathbf{E}), \dots, f_n(\mathbf{E})\}$$

$$\hookrightarrow \max t, \text{ s.t. } f_k(\mathbf{E}) - t \geq 0$$

Filtering & Projection

to enforce binary-constrained single-layered metagratings.


- Achieved using Sigmund's "hat filter"; approx. to Heaviside step function^[5]
- Threshold parameter β steadily increased for binary convergence



Results & Discussion

Achromatic Metalenses


Tested parameters: 0.1 – 0.5 NA, for visible spectrum of 400-700nm



- ✓ Distinct focusing of broadband light
- ✓ Customisable numerical aperture
- ✓ Adaptable optimisation process + fast processing times (~4.36h)

Achromatic + Wide Fields of View (WFOV)

Tested parameters: 0.3 NA, wavelengths 500–700nm, 15° incidence
Achieved by incorporating k-point wavevector w/ varying amplitude.




- ✓ Adapted to oblique incident planewaves
- ✓ Persistent achromatic characteristics

Conclusion



Computationally-inexpensive and cost-effective approach



Simultaneous realisation of **achromatic functionality** with **wide fields-of-view**

Future Work:

- Multi-layered metalenses (e.g. 2.5D metastructure schematics)
- Expansions on high-NA and WFOV capabilities

References:

- Li, Y. *et al.* (2022). Ultracompact multifunctional metalens visor for augmented reality displays. PhotonIX. <https://doi.org/10.1186/s43074-022-00075-z>
- Chung, H., & Miller, O. D. (2020). High-NA achromatic metalenses by inverse design. Optics Express. <https://doi.org/10.1364/oe.385440>
- Oskooi, A. *et al.* (2009). Meep: A flexible free-software package for electromagnetic simulations by the FDTD method. Computer Physics Communications. <https://doi.org/10.1016/j.cpc.2009.11.008>
- Svanberg, K. (1987). The method of moving asymptotes—a new method for structural optimization. International Journal for Numerical Methods in Engineering.
- Hammond, A. M., Oskooi, A., Johnson, S. G., & Ralph, S. E. (2021). Photonic topology optimization with semiconductor-foundry design-rule constraints. Optics Express. <https://doi.org/10.1364/oe.431188>